

SYSTEMS AND METHODS FOR ADAPTIVE BIT LOADING IN A  
MULTIPLE ANTENNA ORTHOGONAL FREQUENCY DIVISION  
MULTIPLEXED COMMUNICATION SYSTEM

5

Abstract of the Disclosure

In an orthogonal frequency division multiplexed (OFDM) system, a transmitter and/or receiver communicate separate data streams on non-orthogonal spatial channels. Each spatial channel may use the same set of  
10 OFDM subcarriers and may take advantage of the multipath characteristics of the spatial channel allowing the communication of additional data without an increase in frequency bandwidth. Space-frequency subcarrier modulation assignments may be dynamically assigned on a per subcarrier basis as well as a per spatial channel basis to help maximize the data-carrying capacity of the  
15 channel. In some embodiments, each of the spatial channels may be associated with one of a plurality of spatially diverse antennas. In other embodiments, beamforming may be performed to allow the transmission and/or reception of signals within the spatial channels.

"Express Mail" mailing label number: EV 332569264 US

Date of Deposit: December 29, 2003

This paper or fee is being deposited on the date indicated above with the United States Postal Service pursuant to 37 CFR 1.10, and is addressed to the Commissioner for Patents, Mail Stop Patent Application, P.O. Box 1450, Alexandria, VA 22313-1450.